

CPS DECON STATION CHECKLIST						
REFERENCE: SHIP SPECS AND DWG 804-595203 REV A						
SHIP:		DATES OF ASSESSMENT:			LOCATION & STATION #:	
	DESCRIPTION	S	U	COMMENTS	STOCK # OR APL/AEL	
WEATHER DECK TO OCUA						
1	ROUTE MARKERS ARE INSTALLED IN WEATHER AREAS TO INDICATE THE MOST DIRECT ROUTE TO THE NEAREST ACCESS OPENING OF THE DECONTAMINATION STATION.			(NAVSHIP DWG# S2803-980208)		
2	DECONTAMINATION STATION ENTERANCE MARKER IS INSTALLED AT EACH ENTERANCE DOOR.			(NAVSHIP DWG# S2803-980208)		
3	A LABEL PLATE READING "ACCESS TO DECONTAMINATION STATION" IS INSTALLED ON THE WEATHER DOOR ACCESS				(APPENDIX 2 FOR DETAILS)	
4	A LABEL PLATE READING "DECONTAMINATION STATION ENTERANCE FOR RECOVERY FROM CBR ATTACK, ENTER UPON COMMAND" SHALL BE INSTALLED ON THE EXTERIOR DECON STATION ENTERANCE.				(APPENDIX 2 FOR DETAILS)	
5	A WARNING PLATE IS PROVIDED ON THE UPPER HALF OF ALL ACCESS CLOSURES IN THE CPS BOUNDRY, ON BOTH SIDES OF THE DOOR, ON THE WEATHER DECK, READING "WARNING – CPS ZONE BOUNDRY – OPEN/CLOSE WITH CARE TO AVOID INJURY"				(APPENDIX 2 FOR DETAILS)	
6	INTERCOM (ON THE WEATHER DECK)					
	A) INTERCOM AND MICROPHONE				509991117	
	B) BUSY LIGHT AND COVER					
	C) LABEL PLATE INDICATING HANDS FREE OPERATION				(APPENDIX 2 FOR DETAILS)	
7	DOOR (WEATHER TO OCUA):					
	A) 26" * 66" * 9" W/6" FIXED LIGHT					
	B) DEAD LIGHT COVER INSTALLED ON INTERIOR OF DOOR					
	C) DC CLASSIFICATION INSTALLED ON DEAD LIGHT COVER					
	D) DEAD LIGHT SWITCH INSTALLED AND OPERATIONAL				219990096	
	E) DC CLASSIFICATION IS PROVIDED ON BOTH SIDES OF DOOR					
8	COMPARTMENT LABEL IS PROVIDED ABOVE OCUA ACCESS AND IS CORRECT. (LIST COMPARTMENT LABEL IN COMMENTS)					
OUTER CLOTHING UNDRESSING AREA (OCUA)						
9	STATION MARKERS :					
	A) 1, 2, & 3 ARE PROVIDED					
	B) IN A 10" X 18" AREA					
10	HINGED BAG HOLDERS ARE INSTALLED (2 REQUIRED)					
	A) LOCKING PINS ARE INSTALLED AND LOCK HOLDER IN PLACE					
	B) HOLDERS ARE 3' 4" ABOVE DECK (RECOMMENDED)					
11	HINGED STOOL PROVIDED					
	A) NO SPRING OR PADDING					
	B) 14" DIAMETER SEAT					

	DESCRIPTION	S	U	COMMENTS	STOCK # OR APL/AEL
12	1 ½ “ DIA. HANDGRAB PROVIDED NEXT TO THE HINGED STOOL				
13	SCISSOR TRAY AND HOLDER PROVIDED				2-770004242
14	STEP GRATING PROVIDED				
	A) OVER STATION MARKER # 3				
	B) GRATE IS 3” ABOVE DECK				
	C) GRATE IS NON-REMOVABLE				
15	2” DECK DRAIN PROVIDED				
16	INTERCOM				
	A) INTERCOM AND MICROPHONE				509991117
	B) BUSY LIGHT				
	C) LABEL PLATE INDICATING HANDS FREE OPERATION				
17	17 1/8” BY 13 1/8” SHOCK HARDENED MIRROR INSTALLED 4’2” ABOVE THE DECK				
18	DECKS ARE 1/8” CRES DIAMOND PLATE AND SLOPES TOWARD DRAIN				
19	RELAY LANTERN PROVIDED				249990138
20	BULKHEADS				
	A) ARE STAINLESS STEEL AND ARE BUFFED OUT OR PAINTED AND HAVE NO LAGGING				
	B) SHEATHING IS INSTALLED OVER ALL INTERNAL STIFFENERS AND IN THE OVERHEAD.				
	C) SHEATHING SEAMS HAVE CONTINUOUS WELDED BEAM				
21	A) (3) 120W OVERHEAD LIGHTS INSTALLED				6210-00-115-9150
	B) LIGHTS HAVE RIG FOR RED CAPABILITY				
22	BOOT WASH TRAY AND HOLDER PROVIDED				
23	VERIFY CCOL IS PROVIDED AND IS CORRECT				
24	VERIFY COMPARTMENT TARGET IS PROVIDED AND IS CORRECT. (LIST COMPARTMENT LABEL IN COMMENTS)				
25	VENT “E” ON WEATHER BULKHEAD				(APPENDIX 1 FOR DETAILS)
	A) DC CLASSIFICATION REQUIRED				
	B) WIRE MESH INSTALLED				
26	A LABEL PLATE READING “DO NOT BLOCK DECONTAMINATION STATION” SHALL BE INSTALLED ON THE OUTBOARD SIDE OF DOORS LEADING FROM THE INTERIOR OF THE SHIP TO THE OCUA.				(APPENDIX 2 FOR DETAILS)
27	A WARNING PLATE IS PROVIDED ON THE UPPER HALF OF ALL ACCESS CLOSURES IN THE CPS BOUNDRY, ON BOTH SIDES OF THE DOOR, ON THE WEATHER DECK, READING “WARNING – CPS ZONE BOUNDRY – OPEN/CLOSE WITH CARE TO AVOID INJURY”				(APPENDIX 2 FOR DETAILS)
28	DOOR (OCUA TO ICUA):				
	A) 26” * 66” * 9” W/6” FIXED LIGHT				
	B) DC CLASSIFICATION IS PROVIDED ON BOTH SIDES OF DOOR				
29	DOOR (OCUA TO INTERIOR OF SHIP):				
	A) 26” * 66” * 9” W/6” FIXED LIGHT				
	B) DC CLASSIFICATION IS PROVIDED ON BOTH SIDES OF DOOR				

	DESCRIPTION	S	U	COMMENTS	STOCK # OR APL/AEL
30	A LABEL PLATE READING "NO ENTRY EXCEPT AS DIRECTED DURING CONTAMINATION RECOVERY OR EXERCISE" SHALL BE INSTALLED ON THE OUTBOARD SIDE OF DOOR LEADING FROM THE OCUA TO THE ICUA.				(APPENDIX 2 FOR DETAILS)
31	VENT "D" IN DOOR FROM OCUA TO ICUA				(APPENDIX 1 FOR DETAILS)
32	COMPARTMENT LABEL IS PROVIDED ABOVE ICUA ACCESS AND IS CORRECT. <i>(LIST COMPARTMENT LABEL IN COMMENTS)</i>				
	<b>INNER CLOTHING UNDRESSING AREA (ICUA)</b>				
33	HINGED BAG HOLDER IS INSTALLED (1 REQUIRED)				
	A) LOCKING PINS ARE INSTALLED AND LOCK HOLDER IN PLACE				
	B) HOLDERS ARE 3' 4" ABOVE DECK (RECOMMENDED)				
34	SCISSOR TRAY AND HOLDER PROVIDED				2-770004242
35	2" DECK DRAIN PROVIDED				679990055
36	INTERCOM				
	A) INTERCOM AND MICROPHONE				509991117
	B) BUSY LIGHT				
	C) LABEL PLATE INDICATING HANDS FREE OPERATION				
37	DECKS ARE 1/8" CRES DIAMOND PLATE AND SLOPES TOWARD DRAIN				
38	RELAY LANTERN PROVIDED				249990138
39	BULKHEADS				
	A) ARE STAINLESS STEEL AND ARE BUFFED OUT OR PAINTED AND HAVE NO LAGGING				
	B) SHEATHING IS INSTALLED OVER ALL INTERNAL STIFFENERS				
	C) SHEATHING IS INSTALLED IN THE OVERHEAD IF STRUCTURAL CEILING IS GREATER THAN 96"				
	D) SHEATHING SEAMS HAVE CONTINUOUS WELDED BEAD				
40	A) (2) 60W OVERHEAD LIGHTS INSTALLED				6210-01-283-0375
	B) LIGHTS HAVE RIG FOR RED CAPABILITY				
41	VERIFY CCOL IS PROVIDED AND IS CORRECT				
42	VERIFY COMPARTMENT TARGET IS PROVIDED AND IS CORRECT. <i>(LIST COMPARTMENT LABEL IN COMMENTS)</i>				
43	15" BY 21" WINDOW(S) IS/ARE INSTALLED AND ARE SEALED				
44	A LABEL PLATE READING "DO NOT OPEN THIS DOOR UNTIL ORDERED TO DO SO BY STATION ATTENDENT: SHALL BE INSTALLED ON THE DOOR LEADING FROM THE ICUA TO SHOWER.				(APPENDIX 2 FOR DETAILS)
45	COMPARTMENT LABEL IS PROVIDED ABOVE SHOWER ACCESS AND IS CORRECT. <i>(LIST COMPARTMENT LABEL IN COMMENTS)</i>				
46	VENT "C" IN DOOR FROM ICUA TO SHOWER				
47	DOOR (ICUA TO SHOWER):				
	A) 26" * 66" * 9" W/6" FIXED LIGHT				
	B) DC CLASSIFICATION IS PROVIDED ON BOTH SIDES OF DOOR				

	DESCRIPTION	S	U	COMMENTS	STOCK # OR APL/AEL
	<b>SHOWER AREA</b>				
48	PORTABLE GRATING IS PROVIDED				
49	FRESH WATER SUPPLY FAUCET IS:				
	A) 24" ABOVE THE GRATING				
	B) HAS A THREADED NOZZLE (FOR ATTACHMENT OF GARDEN HOSE)				
50	4" DECK DRAIN				
51	MULTI NOZZLE SHOWER				
	A) LOWEST NOZZLE IS 8" ABOVE GRATING				
	B) 8 PIPE HANGERS				
	C) 28 SPRAY NOZZLES				
52	BULKHEADS				
	A) ARE STAINLESS STEEL AND ARE BUFFED OUT OR PAINTED AND HAVE NO LAGGING				
	B) SHEATHING IS INSTALLED OVER ALL INTERNAL STIFFENERS				
	C) SHEATHING IS INSTALLED IN THE OVERHEAD IF STRUCTURAL CEILING IS GREATER THAN 96"				
	D) SHEATHING SEAMS HAVE CONTINUOUS WELDED BEAD				
53	A) (1) 60W OVERHEAD LIGHTS INSTALLED				
	B) LIGHTS HAVE RIG FOR RED CAPABILITY				
54	DECKS ARE 1/8" CRES DIAMOND PLATE AND SLOPES TOWARD DRAIN				
55	VERIFY CCOL IS PROVIDED AND IS CORRECT				
56	A LABEL PLATE READING "USE HANDS TO SHIELD CANISTER (S) DURING SHOWER OPERATION. CAUTION: DO NOT TOUCH CANISTER (S)" SHALL BE INSTALLED UNDER THE CONTROL WINDOW IN THE SHOWER AREA.				SEE APPENDIX 2 FOR DETAILS
57	VERIFY COMPARTMENT TARGET IS PROVIDED AND IS CORRECT. (LIST COMPARTMENT LABEL IN COMMENTS)				
58	15" BY 21" WINDOW(S) IS/ARE INSTALLED AND ARE SEALED				
59	A LABEL PLATE READING "DO NOT OPEN THIS DOOR UNTIL ORDERED TO DO SO BY STATION ATTENDENT: SHALL BE INSTALLED ON THE DOOR LEADING FROM THE SHOWER TO THE CPL.				
60	DOOR (SHOWER TO CPL):				
	A) 26" * 66" * 9" W/6" FIXED LIGHT				
	B) DC CLASSIFICATION IS PROVIDED ON BOTH SIDES OF DOOR				
61	COMPARTMENT LABEL IS PROVIDED ABOVE CPL ACCESS AND IS CORRECT. (LIST COMPARTMENT LABEL IN COMMENTS)				
62	VENT "B" IN DOOR FROM SHOWER TO CPL				
	<b>CONTAMINATION PURGE LOCK (CPL)</b>				
63	PORTABLE GRATING IS PROVIDED				
64	2" DECK DRAIN				
65	DECKS ARE 1/8" CRES DIAMOND PLATE AND SLOPES TOWARD DRAIN				
66	RELAY LANTERN PROVIDED				

	DESCRIPTION	S	U	COMMENTS	STOCK # OR APL/AEL
67	INTERCOM				
	A) INTERCOM AND MICROPHONE				
	B) BUSY LIGHT				
	C) LABEL PLATE INDICATING HANDS FREE OPERATION				
68	BULKHEADS				
	A) ARE STAINLESS STEEL AND ARE BUFFED OUT OR PAINTED AND HAVE NO LAGGING				
	B) SHEATHING IS INSTALLED OVER ALL INTERNAL STIFFENERS				
	C) SHEATHING IS INSTALLED IN THE OVERHEAD IF STRUCTURAL CEILING IS GREATER THAN 96"				
	D) SHEATHING SEAMS HAVE CONTINUOUS WELDED BEAD				
69	A) (1) 60W OVERHEAD LIGHTS INSTALLED				6210-01-283-0375
	B) LIGHTS HAVE RIG FOR RED CAPABILITY				
70	VERIFY COMPARTMENT TARGET IS PROVIDED AND IS CORRECT. (LIST COMPARTMENT LABEL IN COMMENTS)				
71	VERIFY CCOL IS PROVIDED AND IS CORRECT				
72	DECONTAMINATION STATION EXIT MARKERS SHALL BE INSTALLED ON THE INTERIOR OF THE EXIT DOOR				DWG S2803-980208
73	A LABEL PLATE READING "DO NOT BLOCK DECONTAMINATION STATION" IS INSTALLED ON THE OUTBOARD SIDE OF DOORS LEADING FROM THE INTERIOR OF THE SHIP TO THE CPL				SEE APPENDIX 2 FOR DETAILS
74	15" BY 21" WINDOW(S) IS/ARE INSTALLED AND ARE SEALED				
75	A LABEL PLATE READING "NO ENTRY EXCEPT AS DIRECTED DURING CONTAMINATION RECOVERY OR EXERCISE" SHALL BE INSTALLED ON THE DOOR LEADING FROM THE INBOARD SIDE OF THE DOOR LEADING FROM THE INTERIOR OF THE SHIP TO THE CPL.				
76	A WARNING PLATE IS PROVIDED ON THE UPPER HALF OF ALL ACCESS CLOSURES IN THE CPS BOUNDARY, ON BOTH SIDES OF THE DOOR, ON THE WEATHER DECK, READING "WARNING - CPS ZONE BOUNDARY - OPEN/CLOSE WITH CARE TO AVOID INJURY"				
77	DOOR (CPL TO PASSAGEWAY):				
	A) 26" * 66" * 9" W/6" FIXED LIGHT				
	B) DC CLASSIFICATION IS PROVIDED ON BOTH SIDES OF DOOR				
78	VENT "A" IN DOOR FROM CPL TO PASSAGEWAY				
ATTENDANTS STATION					
79	SOUND POWERED TELEPHONE IS PROVIDED WITH HANDSET				
80	MASTER CONTROL BOX OF THE 75MC IS PROVIDED				509991117
81	RELAY LANTERN PROVIDED				
82	FOLLOWING LOCKERS ARE LOCATED ON THE CLEAN SIDE VESTIBULE OUTSIDE EACH CBR DECON STATION OR AS CLOSE AS PRACTICE:				
	A) (1) TYPE "A" CLOTHES LOCKER				
	B) (1) MEDICAL LOCKER				
83	LIGHT SWITCH CONTROLLING LIGHTS IN ICUA/SHOWER/CPL				219990457

	DESCRIPTION	S	U	COMMENTS	STOCK # OR APL/AEL
84	3 POSITION LIGHT SWITCH PROVIDING RED LIGHT/ WHITE LIGHT/ OR NO LIGHT CAPABILITIES TO THE OCUA				219990564
85	AIR TEST FITTING PROVIDED WITH "X" DC CLASSIFICATION				
86	35 PSIG CAN BE MAINTAINED ON THE SEAWATER CONNECTION				
87	REDUCING VALVE IS CORRECTLY SET TO 35 PSI				
88	SHOWER GAGE IS RED LINED AT 35 PSI				
89	BACKFLOW PREVENTOR (VACCUUM BREAKER:				
	A) HAS ISOLATION CAPACITY				
	B) DOES NOT CONTINUOUSLY LEAK				
90	FRESH WATER CONNECTION CAN BE DEMONSTRATED				
91	HOSE QUICK DISCONNECTS ARE PROVIDED AND CAN BE ATTACHED TO BOTH FRESHWATER AND SEAWATER WITH NO LEAKING				
92	SHOWER PIPING IS LABELED				
	A) SEA WATER				
	B) FRESH WATER				
93	FRESH & SEA WATER DOES NOT LEAAK ONTO THE SHOWER GAGES AND 75MC WHILE CHANGING THE HOSE FROM FRESH WATER TO SEA WATER				
94	DECK DRAIN IS PROVIDED				679990055
95	DECK DRAINS ARE:				
	A) A MINIMUM OF 6"				
	B) INDIVIDUALLY TRAPPED				
	C) INDIVIDUALLY COUPLED				
	D) PIPED INDIVIDUALLY OVERBOARD INDEPENDANT OF ALL OTHER DRAINS.				
96	CORRECT STENCILING FOR DECON STATION PIPING LEADING OVERBOARD				
97	OVERBOARD DRAIN VALVE				
	A) HAS CORRECT DC CLASSIFICATION "W"				
	B) QUICK ACTING VALVE IS PROVIDED				
98	LABEL PLATES AT THE QUICK DISCONNECT STATION:				
	A) POTABLE WATER SUPPLY FOR FLUSHING THE SHOWER				SEE APPENDIX 2 FOR DETAILS
	B) SEA WATER SUPPLY FOR PERSONNEL DECONTAMINATION				SEE APPENDIX 2 FOR DETAILS
99	LABEL PLATE (INSTRUCTION PLATE): SHOWER: 30 SECONDS AT 35 PSI PURGE LOCK TIME: 2 MINUTES				
100	BRACKET FOR 50 FT ¾" GARDEN HOSE				

	DESCRIPTION	S	U	COMMENTS	STOCK # OR APL/AEL				
	CBR DECONTAMINATION EQUIPMENT INVENTORY								
101	THE FOLLOWING ITEMS ARE REQUIRED PER STATION				2-770004242				
A	{ 1 BX } BAG, PLASTIC 10 GAL				8105-01-183-9765				
B	{ 1 BX } BAG, PLASTIC 55 GAL				8105-01-183-9764				
C	{ 3 EA } BRUSH, SCRUB DK				7920-00-240-7171				
D	{ 2 EA } BRUSH, BOOT WASH				7920-00-255-7536				
E	{ 48 EA } CALCIUM HYPOCHLORITE				6810-00-255-0471				
F	{ 2 KITS } CP-KIT, M256A1 DETECTOR				6665-01-133-4964				
G	{ 1 BOX (20 KITS)} CP-KIT, M291 DECON				6850-01-276-1905				
H	{ 1 KIT } DECON KIT, M258A1				4230-01-101-3984				
I	{ 1 GAL CAN } GENERAL DETERGENT				7930-00-282-9699				
J	{ 3 EA } HANDLE DECK BRUSH				7920-00-141-5452				
K	{ 1 EA } HOSE ASSEMBLY, NONME				4720-00-230-6577				
L	{ 1 EA } MEASURE, LIQUID, 8 OZ CAP				7240-00-138-7983				
M	{ 2 ROLLS } M9 PAPER, CA DETECTION				6665-01-226-5589				
N	{ 1 EA } NOZZLE, GARDEN HOSE				4730-00-223-6731				
O	{ 2 EA } PAIL, UTILITY, 5 GAL				7240-01-094-4305				
P	{ 2 EA } PAN, STEAM TABLE (SCISSOR TRAYS)				7310-00-576-4614				
Q	{ 2 ROOLS } PRESS SEN TAPE 2 IN				7510-00-266-6710				
R	{ 12 EA } SCISSORS, BANDAGE				6515-00-935-7138				
S	{ 3 EA } SPONGE, CELLULOSE				7920-00-240-2555				
T	{ 1 ROLL } TAPE, DUCT, 2 IN WIDE				5640-00-103-2254				
U	{ 1 LB } TWINE-HEMP FIBROUS				4020-00-231-5870				
	CBR PERSONNEL PROTECTION EQUIPMENT INVENTORY								
	AOE-6 CLASS = 2-770004244	DDG-51 CLASS = 2-770004248 (COL 1)		LHD-1 CLASS = 2-770004249 (COL 1)	LSD-49 CLASS = 2-770004250				
	AOE-8 = 2-770004243	LHA-1 = 2-77004248 (COL 8)		LSD-41 CLASS = 2-770004249 (COL 8)					
102	THE FOLLOWING ITEMS ARE REQUIRED PER SHIP CLASS:								
		4243	4244	4248	4249	4250			
				“1”	“8”	“1”	“8”		
A	ATROPINE INJECTION	****	****	****	****	****	****	PER NAVMED P-5041	6505-00-926-9083
B	BELT, WEBB,SZ LG	1132	268	364	864	962	353	428	8465-01-322-1966
C	BELT, WEBB,SZ MED	200	48	65	153	170	63	76	8465-01-322-1965
D	CANTEEN, WATER 1QT	1332	315	428	1016	1131	415	504	8465-01-115-0026
E	COVER, WATER CANTEEN	1332	315	428	1016	1131	415	504	8465-00-860-0256
F	CP-CANISTER, MCU-2A/P,C2	AR	45	AR	3047	AR	AR	AR	4240-01-361-1319
G	CP-FOOTWEAR COVERS	NL	315	428	1016	1131	415	504	8430-01-021-5978
H	CP-GLOVE SET, SZ L	555	132	179	762	849	312	378	8415-01-033-3519
I	CP-GLOVE SET, SZ M	698	165	224	958	1067	392	475	8415-01-033-3518
J	CP-GLOVE SET, SZ S	222	53	72	305	340	125	151	8415-01-033-3517
K	CP-GLOVE SET, SZ XL	111	27	36	153	170	63	76	8415-01-033-3520
L	CP-KIT,M291 DECON {BOX}	91	22	30	70	77	31	34	6850-01-276-1905
M	CP-MASK, MCU-2A/P SZ L	280	67	90	214	238	88	106	4240-01-327-4150
N	CP-MASK, MCU-2A/P SZ M	826	196	265	630	702	258	312	4240-01-327-4149

